





RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

TABLE2:
PINS DESCRIPTION,ONLY USED FOR 3.1 SERIES.

A12	A11	A10	A9	A8	A7	A6	A5	A4	A3	A2	A1
GND	RX2+	RX2-	VBUS	SBU1	D-	D+	CC	VBUS	TX1-	TX1+	GND
GND	TX2+	TX2-	VBUS	Vconn			SBU2	VBUS	RX1-	RX1+	GND
B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12

REV

A

DESCRIPTION

新版发行

DATE

2023. 01. 06

APPROVED

HHM

NOTES:

1. Material:SEE TABLE1;
2. Plating specification,
 - 2-1. Contact:
Contact area: Ni50u"Min/Au See Table3;
Solder area: Ni50u"Min/Sn100u"Min.
Other area: Ni 50u"Min.
 - 2-2. Shell: Ni50u"~150u";
 - 2-3. Latch:
Solder area: Ni50u"Min/Sn100u"Min.
Other area: Ni 50u"Min.
3. Mechanicl Performance ,
 - 3-1. Insertion Force:5~20N;
 - 3-2. Extraction Force:8~20N after 10000 cycles;
 - 3-3. Durability:10000 cycles.
4. Electrical Performance,
 - 4-1. Insulation Resistance:100MΩ Min.
 - 4-2. Contact Resistance :50mΩ Max.
 - 4-3. Dielectric Strength :100V AC.
 - 4-4. Current:15A .
5. The product accords with ROHS STD.

TABLE1:

6	EMC SPRING	Stainless Steel;SUS301,T=0.08mm;
5	CONTACT-2	Copper Alloy;AuNiSn;T=0.15mm(Signal)
4	CONTACT-1	Copper Alloy;AuNiSn;T=0.25mm(Current)
3	LATCH	Stainless Steel;SUS301,T=0.40mm;
2	HOUSING	LCP Thermoplastic,UL94V-0;
1	SHELL	Stainless Steel;SUS316L,T=0.15mm;
NO.	NAME	DESCRIPTION

CUSTOMER DRAWING

UNITS mm	SCALE 1:1	SHEET 1 OF 1
PROJECTION: 	DRAW: DAP	
GENERAL TOLERANCE 0. ±0.35 0.0 ±0.25 0.00 ±0.15 0.° ±4° 0.0° ±3°	CHECK: HWT APPD: HHM	

铭创科技（东莞）有限公司

Mingchuang Technology (Dongguan) Co., Ltd.

TITLE

TYPE C公头24PIN 夹板0.8 15A大电流 L=10.6

MAT'L

SEE TABLE

FINISH

SEE TABLE

DWG. NO.

1051. TCM. 16JB. H5

PART NO.

SIZE

A4