


REV	DESCRIPTION	DATE	APPROVED
A	新版发行	2020. 11. 06	HHM

NOTES:

- MATERIAL: SEE "TABLE 1";
- FINISH: SEE "TABLE 1";
- ELECTRICAL :
 - CONTACT CURRENT RATING :
 - 3A MAX FOR VBUS PIN ;
 - 1.25A MAX FOR GND PIN;
 - 0.25A MAX FOR OTHER PIN;
 - INSULATION RESISTANCE :
 - 100 MEGAOHMS MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE :
 - 100V AC MAX
 - CONTACT RESISTANCE : 40mΩ MAX.
- MECHANICAL CHARACTERISTICS :
 - MATING FORCE: 5~20N.;
 - UNMATING FORCE: 8~20N(INITIAL), 6~20N(AFTER 10000 CYCLES);
 - DURABILITY : 10,000 MATING CYCLES.
 - OPERATING TEMPERATURE : -40° C TO +80° C
- WATER PROOFNESS: THIS PRODUCT IS BASED ON IPX7.
- PACKAGING: TAPE & REEL.



ITEM	PART NAME	Q' TY	FINISH	NOTE
5	MID PALTE	1	SUS301	T=0.15mm
4	O RING	1	SILICON RUBBER	RED
3	Shell	1	ZINC ALLOG Ni 40-80u"	WHITE
2	Contact	16	C7025 Ni 50U"; Au 3U"Plating	T=0.15mm
1	Housing	1	PA10T (G.F30%)	BLACK

CUSTOMER DRAWING			铭创科技(东莞)有限公司		
UNITS mm	SCALE 1:1	SHEET 1 OF 2	Mingchuang Technology (Dongguan) Co., Ltd.		
PROJECTION: 	DRAW: DAP		TITLE 防水TYPE C母座16PIN 板上四脚插板SMT L=6.5 舌片外露 锌合金		
GENERAL TOLERANCE .000 ±0.20 .00 ±0.30 .0 ±0.50 .0 ±2° .00 ±1°	CHECK: HWT	MAT'L SEE TABLE	FINISH SEE TABLE		
	APPD: HHM	DWG. NO. B09W1602A	PART NO.	SIZE A4	